

EPIC® MC module: PROFIBUS DP

The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and rack technology.

PROFIBUS DP module is suitable for continuous bus operation and has screw termination, which ensures easy installation.

Info

Profibus DP module for uninterrupted fieldbus operation
 Locking lever for rapid removal of the module



Wind Energy



Industrial machinery and plant engineering



Automation & fältinstallation

Benefits

Uninterrupted fieldbus operation when pulling the connector
 Transmission rate up to 12 MBit/s
 Easy assembly with screw connection
 Shielding connection by strain relief clamp

Application range

Plant construction
 Event equipment
 Control engineering

EPIC® MC module: PROFIBUS DP

Technical Data

| | |
|---------------------|---|
| Classification: | ETIM 5.0 Class-ID: EC002641 ETIM 5.0 Class-Description: Modular connector (industrial connector) |
| Rated voltage (V): | 30 V |
| Rated current in A: | 1 A |
| Pollution degree: | 3 |
| Contacts: | Copper alloy, gold-plated |
| Number of contacts: | 2 / 4 + shielding |
| Cable connection: | Screw connection, for Profibus cable |
| Plug cycles: | 100 |
| Temperature range: | -20 °C do +85 °C |

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® MC module: PROFIBUS DP

| Article number | Article description | Contact type | Number of working contacts | Slots |
|---------------------|---------------------|--------------|----------------------------|-------|
| Module: Profibus DP | | | | |
| 10390400 | MCS 2 SS | male | 2 + shield | 1 |
| 10390500 | MCS 2 BS | female | 2 + shield | 1 |

Last Update (11.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16