Documentation

Prevost



Markets Services

Home > Distribution > Hose reels > DGO series - Large - Rubber hose

## **DGO SERIES - LARGE - RUBBER HOSE**

### ₽

\*

Q

Technical characteristics Technology : Pipe locked with Max operating pressure : 12 bar ratchet stop Construction : Epoxy-coated steel case Connection : 1 m of inlet supply Equipped with : Fixed bracket hose Fixed bracket



DESCRIPTION

Inlet : G 3/8 F

+ 1 m hose Pressure : 12 bar

Inlet : G 1/2 M for DGO 1320 + DGO 1610

Temperature : -15°C to +65°C

| ID/OD (mm) | Length (m) | Coupler | Flow rate (I/min) | Swivel inlet (BSPP) | Weight (kg) | Part numbers |
|------------|------------|---------|-------------------|---------------------|-------------|--------------|
| 10 x 17    | 25         | ESI 07  | 500               | G 3/8 F             | 26          | DGO 1025ES   |
| 13 x 20    | 20         | ESI 07  | 1000              | G 1/2 M             | 27          | DGO 1320ES   |
| 16 x 23    | 10         | ESI 11  | 3000              | G 1/2 M             | 27          | DGO 1610ES   |
| 10 x 17    | 25         | ISI 06  | 500               | G 3/8 F             | 26          | DGO 1025 S   |
| 13 x 20    | 20         | ISI 08  | 1000              | G 1/2 M             | 27          | DGO 1320IS   |
| 16 x 23    | 10         | ISI 11  | 3000              | G 1/2 M             | 25          | DGO 1610IS   |
| 10 x 17    | 25         | CSI 06  | 500               | G 3/8 F             | 26          | DGO 1025CS   |
| 13 x 20    | 20         | CSI 08  | 1000              | G 1/2 M             | 27          | DGO 1320CS   |
| 16 x 23    | 10         | ISG 11  | 3000              | G 1/2 M             | 25          | DGO 1610     |
|            |            |         |                   |                     |             |              |

#### DIMENSIONS



Model to be installed at each needed points of use

| A (mm) | B (mm) | C (mm) | Part numbers |
|--------|--------|--------|--------------|
| 485    | 480    | 237    | DGO 1025ES   |
| 485    | 480    | 237    | DGO 1320ES   |
| 485    | 475    | 237    | DGO 1610ES   |
| 485    | 480    | 237    | DGO 1025IS   |
| 485    | 480    | 237    | DGO 1320IS   |
| 485    | 480    | 237    | DGO 1610IS   |
| 485    | 480    | 237    | DGO 1025CS   |
| 485    | 480    | 237    | DGO 1320CS   |
| 485    | 480    | 237    | DGO 1610     |
|        |        |        |              |





# INTERESTED? NEED MORE INFORMATION?

A question about a product? About its use or characteristics? The Prevost team replies to your questions.

CONTACT AN EXPERT

## SUPPORT AND DOCUMENTS

A question about the company? Concerning a product? About its use or characteristics? You will find an answer in the FAQs or our document database.

We have also gathered professional advice to respond to your needs. Do not hesitate to consult them.

DOCUMENTATION

## prevost

Prevost, the French leader for quick safety couplings, has become the reference partner for industries using pneumatic and hydraulic power. Capitalising on 40 years of experience, we are able to offer tailored and effective products and services.

FIND OUT MORE ABOUT PREVOST

CONTACT US

Recruitment - News - Contact details - Terms - Privacy Policy - Cookies

### DIRECT ACCESS

- > Quick couplings and adaptors for compressed air
- > Hose reels for compressed air, water...
- > Compressed-air blowguns
- > Compressed air tools
- > Compressed air pipe and fitting
- > Hoses and extension hoses

#### STAY CONNECTED

I would like to be informed about new Prevost products

| Email | OK |
|-------|----|

All rights reserved Prevost 2017 ©