



SICMEMOTORI

PAG. 1 / 1

ELECTRICAL DATA

POWER (KW) :18,40/
ARM. VOLT. (V) :440,00/
SPEED (RPM) :1750/
ARM. CURR. (A) :

NO. OF POLES : 4

MECHANICAL DATA

ENVIRONMENT : NORMAL ENVIRONMENT
MOUNTING (IM) : 1001 B3
PROTECTION (IP) : 23 S
FAN SUPPLY : 230/400V +/- 10% 50HZ THREEPHASE
DIRECT COUPLING
VIBRATION GRADE : N
SHAFT MATERIAL : STANDARD
D.E. SHAFT : STANDARD
D.E BEARING : BALL

COOLER MOUNTING : TOP
TERMINAL BOX : STANDARD - RIGHT

INCORPORATED ACCESSORIES

THERMAL PROTECTION: 1-KLIXON ON AUXILIARY POLE
FILTER

ACCESS. PROVISIONS

PROVISION FOR TACHO/ENCODER: WITH COUPLING
TACHOG./ENCODER : REO 444R1-60 V/1000 RPM D11

GENERAL DATA

REFERENCE TEMP. : 40 C.
OUTLINE DRAWING :
PACKING : ON PALLET

DUTY : S1
SUPPLY : T.F.C.B.
ECCITAZ. : SEPARATE WITHOUT STAB.SERIES

INS. CLASS : H DT H
FIELD VOLT(V): 220,00/0,00

ALTITUDE (MT.) : 1000

COOLING (IC) : 06 PVA

PAINTING : SPECIAL - CYCLE 1A
RAL : 5015

PRESSURE SWITCH

- SUPPLY -

ELECTRIC STANDARDS. : CEI,IEC
NAMEPLATE : ENGLISH