

Conductor marker carrier - PATO 1/10 - 1013876

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Conductor marker carrier, transparent, unlabeled, Mounting type: clip on, Cable diameter: 2-3.5 mm, Lettering field: 4 x 10 mm

The figure shows a similar product

Why buy this product

- Can be labeled using UC-WMT ... and US-WMT ... plastic labels or EMT insert strips
- These marking collars are used for subsequent labeling of systems that have already been wired

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	1000 STK
GTIN	 4 017918 014063
GTIN	4017918014063
Weight per Piece (excluding packing)	0.290 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Dimensions

Width (a)	10 mm
Cable diameter	2 mm ... 3.5 mm

Ambient conditions

Ambient temperature (operation)	-50 °C ... 80 °C
---------------------------------	------------------

General

Conductor marker carrier - PATO 1/10 - 1013876

Technical data

General

Color	transparent
Components	Silicone-free
Flammability rating according to UL 94	V0
Material	PVC
RoHS compliant	Yes
Marking mounting type	clip on

Standards and Regulations

Flammability rating according to UL 94	V0
--	----