

Product name VEGASWING 51
 Model code SG51.XXSGATPV
 eID DE49628308
 Quantity 1

Vibrating level switch for liquids

Application area

VEGASWING 51 is used as a universal level switch in liquids with small dimensions. Independent of the mounting position, it detects reliably with millimetre accuracy the limit level. The instrument can be used as empty or full detector, as approved overfill protection, dry run protection or pump protection in vessels and pipelines. The VEGASWING 51 is an economical solution with maximum reliability and safety.

Your benefit

- Minimum time and cost expenditure thanks to simple setup without medium
- Precise and reliable function due to product-independent switching point
- Low maintenance costs

Price list: Standard-11/10/2019-DE-€

| | | |
|--|-----------|--|
| Approval directive / Scope | | None / World-wide |
| Approval | XX | without |
| Version / Process temperature | S | Standard / -40...+100°C |
| Process fitting / Material | GA | Thread G1 PN64, DIN3852-A / 316L |
| Electronics | T | Transistor PNP 9.6 ... 35 V DC |
| Housing | P | 316L |
| Electrical connection / Protection | V | according to ISO4400 incl. plug / IP65 |
| Switching point | | Standard |
| Operating instructions | | DE - German |
| Number of operating instructions | | 1 |
| Measurement loop identification label | | without |
| Additional cleaning procedure | | without |
| Certificate / Standard | | without |
| Foodstuff/Pharmaceutical certificate | | without |
| Setting of the density range | | Standard sensitivity (from density 0.7 g/cm ³) |
| Switching delay in seconds | | 0,5 |
| Recommended welded socket (not in scope of delivery) | | ESTSG.1GA** |
| Customs tariff number (HS code) | | 90261029 |