

Product data sheet



PROGRAMME MOSAIC LEGRAND

Multi-support single socket Mosaic -German std - 2P+E special screw term. -2 mod
REF. 077213 | EAN. 3245060772130

Mosaic™ Programme mechanisms - multi-support single and multiple sockets: German standard- White

4,12 € / Vienetas

Rekomenduojama kaina
Be PVM

> [The product details page](#)

Pagrindinis aprašymas:

Mosaic™ Programme mechanisms - multi-support single and multiple sockets: German standard- White

Produkto savybės:

- Mosaic™ Programme mechanisms - multi-support single and multiple sockets: German standard
- Multi-support single sockets - German standard- For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension, office module and trunking2P+E with shutters for child protection - White- with special tap-off screw and 4 mm² screw terminals- Can be installed in receptacles for floor sockets

Techninės charakteristikos

Model	Socket outlet CEE 7/3 (type F)
Concurrently switching neutral conductor	No
Protective contact	Other
Number of active contacts (round)	2
Number of active contacts (flat)	0
Number of active contacts (square)	0
With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of units	1
Number of modules (module system)	2
Number of socket outlets switchable	0

Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	No
Colour of switch operator	White
Rotated central insert	No
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04

Number of phases	1
Imprint/indication	None
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No
Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	No special power supply
Mounting method	Module frame
Type of fastening	Snap mounting (engagement)
Material	Plastic
Material quality	Thermoplastic

Device width	45 mm
Device height	45 mm
Device depth	39.5 mm
Min. depth of built-in installation box	40 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	31 mm
Operating / setting temperature	-5-35 °C
Storage temperature	-10-70 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section	4-4 mm ²
Cable support	Other
Assembly arrangement	Basic element with central cover plate
Connected object	No

Dokumentacija

Techniniai dokumentai

→ F00754EN-10.pdf | PDF (0.54Mo)

Sutartys ir sertifikatai

→ NEMKO-P14218574 | (0.21Mo)

→ IRAM-DC-E-E100-002.1C1 | (1.04Mo)

→ OC / CB-HU-003962 | (0.48Mo)

→ OC / CB-HU-001259-A4/M1 | (0.12Mo)

→ LGRP-00075-V01.01-EN.pdf | PDF (0.7Mo)

→ OC / CB-HU-005369 | (0.78Mo)

CAD ir projektavimo specifikacijos / BIM

→ 3D_LG-077213.stp | IFC (3.84Mo)

- VDE-40036340 | (0.29Mo)
- MEEI-UP 69259699 0001 | (0.52Mo)
- OC / CB-HU-001259 | (0.59Mo)