

## Hermetically Sealed Point Level Switches Actuated By The Magnicator® Float

- Easy installation – Clamps to Magnicator chamber
- Latches to maintain position as the float passes
- Field adjustable
- No contact with process

Jerguson Magnicator gives you the most accurate and dependable electrical interface for point level control or alarm on a Magnetic Level Indicator.

This simple reed switch device can be used as an input to user-supplied controllers or DCS systems. Available with either SPDT or DPDT action, the RS-2 and RS-2/2 are designed to give years of trouble-free service.

### Model RS-2 or RS-2/2 Reed Switch

- Hermetically Sealed Bi-Stable Latching Reed Switch
- Maximum 1 Amp, Current Load @ 150 VAC/VDC, 25W Max
- Completely Sealed – Never has to be opened or exposed to the environment
- UL/CUL approved for service in Class I, Division 1 Groups B, C, & D; Class II, Division 1 Groups E, F, & G Hazardous Locations

Represented By:  
Yates & Company, Inc.  
1 Hollywood Avenue, Unit 22  
HoHoKus, NJ 07423  
PH: 201-345-3101  
Info: YATESCO.NET



### Model RS-2 or RS-2/2 Specifications

Maximum Voltage:	150 VAC/VDC
Maximum Current:	1.0 Amp
Maximum Power:	25 Watts
Deadband:	.375"
Max. Temp. (Process):	Temperature above 300°F (150°C) require special mounting & Insulation options.
Minimum Temperature:	-40°F (-40°C)
Enclosure:	NEC Class I, Division 1, Groups B, C, & D NEMA 4X
Contacts:	RS-2 or RS-2/2
Conduit Connection:	¾" NPT